

SUPERIOR CLEANING



Ergonomic
design



Low water
consumption



Large
opening



Low energy
consumption

FEATURES

- ✓ Freestanding, high spin
- ✓ Stainless steel top panel & anthracite grey front and side panels
- ✓ Stainless steel drum and tub
- ✓ Basic - easy to use control
- ✓ Large drain valve (ø 76 mm) – easy access to all vital parts from the front
- ✓ Large door opening for easy loading & unloading
- ✓ Patented soap hopper



OPTIONS

- Professional control – free programmable
- Stainless steel front and side panels
- USB plug (on the back panel)
- Liquid soap print – liquid soap connections
- Automatic door opening in case of power failure
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- Drain pump
- Cashless payment system (CPS)



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

INNERDRUM	Maximum capacity 1:9	kg 9
	Capacity 1:10	kg 7,5
	Volume	litres 75
	Diameter	mm 530
DRUM SPEED	Wash speed	rpm 49
	Extraction speed	rpm 1086 (1165)
	G-factor spin speed	350 (optional 400)
HEATING	Electricity (standard)	kW 6 / 9
	Steam	bar 1-8
	Hot water	°C 90
	Sound pressure level	db (A) < 65
	Water valves connection	BSP 3/4 "
	Water pressure	kPa 100-800
	Rec. water pressure	kPa 300-500
	Water inlet	l/min 20
	Drain valve	outer Ø mm 76
	Flow amount with drain valve	t/min 210
	Steam valve connection	BSP 1/2
	Steam pressure	kPa 100-800
	DIMENSIONS	Size HxWxD
TRANSPORT DATA	Gross	kg 200
	Net	kg 185
	Packed HxWxD	mm 1245 x 750 x 840

- 1 Electrical connection
- 2 Hot water
- 3 Cold water hard
- 4 Cold water soft
- 5 Main switch
- 6 Liquid soap connection
- 7 Drain
- 8 Soap dispenser
- 9 Control panel
- 10 Button centralstop
- 11 Door opening Ø 330 mm
- 12 Fuses
- 13 USB port
- 14 Electrical connection to liquid soap pumps

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
HS 80	710	726	1115	790	355	230	88	920	1010	113	218	293	390	1020	24