

SUPERIOR CLEANING



Ergonomic
design



Low water
consumption



Fast drying
cyclus



Large
opening



Low electricity
consumption

- ☑ Stainless steel outer and inner drum
- ☑ Industry-leading 440 G-Force extraction removes more moisture, minimizing drying times and utility costs
- ☑ Totally freestanding: can be installed on any floor and any level
- ☑ Suspension with new out-of-balance logic
- ☑ Soap box with four compartments
- ☑ Door opens 180° for easy loading and unloading
- ☑ Standard with drain pump
- ☑ Top, front and side panels standard available in anthracite grey
- ☑ Electrical heating or boiler-fed
- ☑ 6 wash programs
- ☑ Possibility of programming cycle modifier options » Added prewash » Extra wash time » Extra rinse
- ☑ LED indication of the status of the program
- ☑ Time remaining countdown

- ☑ Galvanized steel cylinder
- ☑ Oversized lint filter located in front for easy cleaning
- ☑ Powerful exhaust blower assures short drying times and low operating costs
- ☑ Wide door opening of 180° for easy loading and unloading
- ☑ Top, front and side panels standard available in anthracite grey
- ☑ Electrical or gas heating
- ☑ 4 drying programs
- ☑ LED indication of the status of the program
- ☑ Time remaining countdown

- ☐ Stainless steel front
- ☐ Drain valve
- ☐ Electronic coin operated version



LAUNDRYLION.COM



LAUNDRY LION®

SUPERIOR CLEANING

FEATURES
WASHER EXTRACTORS
FEATURES
DRYERS

OPTIONS

SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

CAPACITY		kg 10
DRUM VOLUME		litres 96,8
MOTOR	Frequency controlled	kW 0,67
EXTRACTION SPEED		rpm 1200
G-FACTOR		440
ELECTRICAL CONNECTION		1x220-240V 50/60 Hz 3x220-240V 50 Hz 3x380-415V 50 Hz 3x380-415V+N 50 Hz
ELECTRICAL HEATING		kW 4,8
DRAIN	Pump	standard
	Drain valve	available
DIMENSIONS	Size HxWxD	mm 1986x683x711
TRANSPORT DATA	Gross weight	kg 193
	Net weight	kg 177
	Cardboard packing	m³ 1,25
	Dimensions (packed) HxWxD	mm 2032x737x832

Standard = Standard version.

