

SUPERIOR CLEANING



Ergonomic
design



Fast drying
cyclus



Large
opening



Low electricity
consumption

FEATURES

- ☑ Galvanized steel cylinder
- ☑ Oversized lint filter located in front for easy cleaning
- ☑ Powerful exhaust blower assures short drying times and low operating costs
- ☑ Wide door opening of 180° for easy loading and unloading
- ☑ Top, front and side panels standard available in anthracite grey
- ☑ Electrical or gas heating
- ☑ 4 drying programs
- ☑ LED indication of the status of the program
- ☑ Time remaining countdown

OPTIONS

- ☐ Stainless steel front
- ☐ Electronic coin operated version



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

CAPACITY		kg 2x10
DRUM VOLUME		litres 2x198
ELECTRICAL CONNECTION		1x220-240V 50/60 Hz 3x220-240V 50 Hz 3x380-415V 50 Hz 3x380-415V+N 50 Hz
ELECTRICAL HEATING		kW 5,2 (230V) 5,3 (400V)
GAS HEATING		kW 7,3
MOTOR POWER		kW 0,25
DIMENSIONS	Size HxWxD	mm 1986x683x737
TRANSPORT DATA	Gross weight	kg 127 (el.) /132 (gas)
	Net weight	kg 120 (el.) /125 (gas)
	Cardboard packing	m³ 1,30
	Dimensions (packed) HxWxD	mm 2032x737x865

Standard = Standard version.

