OPTIONS

SUPERIOR CLEANING



design



Low water consumption



Large opening



Low energy consumption

- ☑ Freestanding, high spin
- ✓ Stainless steel top panel & anthracite grey front and side panels
- ☑ Basic easy to use control
- ☑ Large drain valve (ø 76 mm) easy access to all vital parts from the front
- ☑ Large door opening for easy loading & unloading
- ☑ Patented soap hopper



- □ Professional control free programmable
- □ Stainless steel front and side panels
- USB plug (on the back panel)
- □ Liquid soap print (8x 24V AC signals) liquid soap connections
- Automatic door opening in case of power failure
- □ Liquid soap pumps
- Water recovery kit
- Steam heating version
- Drain pump
- Cashless payment system (CPS)





SUPERIOR CLEANING

INNERDRUM	Maximum capacity 1:9	kg	20
	Capacity 1:10	kg	18
	Volume	litres	180
	Diameter	mm	750
DRUM SPEED			
	Wash speed	rpm	42
	Extraction speed	rpm	915
	G-factor spin speed		350 (optional 400)
HEATING	Electricity (standard)	kW	12/18
	Steam	bar	1-8
	Hot water	°C	90
	Sound pressure level	db (A)	< 65
	Water valves connection	BSP	3/4 "
	Water pressure	kPa	100-800
	Rec. water pressure	kPA	300-500
	Water inlet	l/min	20
	Drain valve	outer Ø mm	76
	Flow amount with drain valve	t/min	210
	Steam valve connection	BSP	1/2
	Steam pressure	kPa	100-800
DIMENSIONS	Size HxWxD	mm	1410x970x970
TRANSPORT DATA	Gross	kg	395
	Net	kg	380
	Packed HxWxD	mm	1550x1025x1015



