

# SUPERIOR CLEANING



Ergonomic  
design



Low water  
consumption



Large  
opening



Low energy  
consumption

## FEATURES

- ✓ Freestanding, high spin
- ✓ Stainless steel top panel & anthracite grey front and side panels
- ✓ Stainless steel drum and tub
- ✓ Basic - easy to use control
- ✓ Large drain valve (ø 76 mm) – easy access to all vital parts from the front
- ✓ Large door opening for easy loading & unloading
- ✓ Patented soap hopper



## OPTIONS

- Professional control – free programmable
- Stainless steel front and side panels
- USB plug (on the back panel)
- Liquid soap print (8x 24V AC signals) – liquid soap connections
- Automatic door opening in case of power failure
- Liquid soap pumps
- Water recovery kit
- Steam heating version
- Drain pump
- Cashless payment system (CPS)



# SUPERIOR CLEANING

## DIMENSIONS & SPECIFICATIONS

<b>INNERDRUM</b>	Maximum capacity 1:9	<b>kg</b> 27
	Capacity 1:10	<b>kg</b> 24
	Volume	<b>litres</b> 240
	Diameter	<b>mm</b> 750
<b>DRUM SPEED</b>	Wash speed	<b>rpm</b> 42
	Extraction speed	<b>rpm</b> 915
	G-factor spin speed	350 (optional 400)
<b>HEATING</b>	Electricity (standard)	<b>kW</b> 18
	Steam	<b>bar</b> 1-8
	Hot water	<b>°C</b> 90
	Sound pressure level	<b>db (A)</b> < 65
	Water valves connection	<b>BSP</b> 3/4 "
	Water pressure	<b>kPa</b> 100-800
	Rec. water pressure	<b>kPa</b> 300-500
	Water inlet	<b>l/min</b> 20
	Drain valve	<b>outer Ø mm</b> 76
	Flow amount with drain valve	<b>t/min</b> 210
	Steam valve connection	<b>BSP</b> 1/2
	Steam pressure	<b>kPa</b> 100-800
	<b>DIMENSIONS</b>	Size HxWxD
<b>TRANSPORT DATA</b>	Gross	<b>kg</b> 450
	Net	<b>kg</b> 430
	Packed HxWxD	<b>mm</b> 1550x1025x1150

- 1 Electrical connection
- 2 Hot water
- 3 Cold water hard
- 4 Cold water soft
- 5 Main switch
- 6 Liquid soap connection
- 7 Drain
- 8 Soap dispenser
- 9 Control panel
- 10 Button CENTRALSTOP
- 11 Door opening Ø 460mm
- 12 Fuses
- 13 USB port
- 14 Electrical connection to liquid soap pumps

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O
HS 240	970	1041	1410	1105	477	270	108,5	1215	1305	102,5	207,5	292,5	610	1315	24