

# SUPERIOR CLEANING



**Ergonomic  
design**



**Low water  
consumption**



**Large  
opening**



**Low electricity  
consumption**

## FEATURES

- ✓ Freestanding, high spin
- ✓ Stainless steel drum and tub
- ✓ Professional – fully programmable microprocessor
- ✓ Large door opening for easy loading and unloading (Ø540 mm)
- ✓ Two large drain valves (Ø76 mm)
- ✓ Frequency controlled motor
- ✓ Perforated lifting ribs: more mechanical action, lower water consumption
- ✓ Ecological washing programmes – significantly reduces water and electricity consumption
- ✓ USB and RS485 plug (on the back panel)
- ✓ Liquid soaps print
- ✓ Soap hopper with 5 removable compartments
- ✓ 3rd water inlet, high inlets capacity
- ✓ Ergonomic height of door enables easy access with trolleys
- ✓ User friendly control position regardless user's height
- ✓ Bumper (front side protection)



## OPTIONS

- Stainless steel front
- Liquid soap pumps
- Traceability software and networking system
- Weighing system by cells
- Recycle drain valve
- Isolation for energy and noise reduction
- Extra signalization (orange light + horn)
- Steam heating version
- Air operated water inlets
- Water sample tap



# SUPERIOR CLEANING

# DIMENSIONS & SPECIFICATIONS

|                       |                             |                          |          |
|-----------------------|-----------------------------|--------------------------|----------|
| <b>INNERDRUM</b>      | Capacity                    | <b>kg</b> 35             |          |
|                       | Volume                      | <b>litres</b> 350        |          |
|                       | Diameter                    | <b>mm</b> 914            |          |
|                       | Depth                       | <b>mm</b> 535            |          |
|                       | Power                       | <b>kW</b> 4              |          |
| <b>DRUM SPEED</b>     | Wash speed                  | <b>rpm</b> 45            |          |
|                       | Extraction speed            | <b>rpm</b> 839           |          |
|                       | G-factor speed              | 360                      |          |
| <b>PROGRAMMER</b>     | Professional                | standard                 |          |
| <b>HEATING</b>        | 100% hot water              | <b>°C</b> 90             |          |
|                       | 100% electrical             | <b>kW</b> 24             |          |
|                       | Steam high pressure         | <b>bar</b> 3-8           |          |
|                       | Electrical                  | <b>3x220-240V</b>        | 50/60 Hz |
|                       |                             | <b>3x380-415V</b>        | 50/60 Hz |
|                       |                             | <b>3x440-480V</b>        | 50/60 Hz |
|                       | Water inlet                 | <b>inch</b> 3x 1"        |          |
|                       | Steam inlet                 | <b>inch</b> 1x 3/4"      |          |
| Drain diameter        | <b>mm</b> outer Ø 76 / 2x3" |                          |          |
| <b>TILTING</b>        | Forward tilting             | n/a                      |          |
| <b>DIMENSIONS</b>     | Size HxWxD                  | <b>mm</b> 1925x1315x1270 |          |
| <b>TRANSPORT DATA</b> | Net weight                  | <b>kg</b> 1010           |          |
|                       | Net weight (w/ tilting)     | <b>kg</b> n/a            |          |
|                       | Gross weight                | <b>kg</b> 1170           |          |
|                       | Gross weight (w/ tilting)   | <b>kg</b> n/a            |          |
|                       | Crate packing HxWxD         | <b>mm</b> 2125x1425x1470 |          |

Standard = Standard version.

The data concerning dimensions of machines include all extended parts.

1. Soap hopper
2. Keyboard
3. Emergency stop
4. Electrical connection
5. Electrical connection to liquid soap
6. Main switch
7. Liquid soap pump connections
8. Air vent tub
9. Water connection
10. Drain valve

