SUPERIOR CLEANING





Low water consumption



Large opening



Low electricity consumption

- **☑** Freestanding, high spin
- ✓ Stainless steel cabinet (AISI 304)
- ✓ Stainless steel drum and tub
- ☑ Professional
 - fully programmable microprocessor
- ∠ Large door opening (HS800, HS1000 Ø530 mm, HS1250 Ø650 mm)
- ☑ Two large drain valves (Ø103 mm)
- ☑ Easy access to all parts
- Standard liquid soap connections
- ☑ Perforated lifting ribs: more mechanical action, lower water consumption
- ☑ Air operated water inlet
- Soap dispenser with 5 removable compartments



OPTIONS

- □ Liquid soap pumps
- □ Traceability software and networking system
- Electrical heating
- □ Forward and backward tilting is available. Tilting of the machine is done by external platform
- □ Tap for water samples
- Automatic weighing system by cells





SUPERIOR CLEANING


CAPACITY	Capacity		120
	Drum volume	liters	1180
	Drum diameter	mm	Ø1300
MOTOR	Frequency controlled		standard
DRUM SPEED	Wash speed	rpm	32
	Spin speed	rpm	695
	G-Factor spin speed		350
PROGRAMMER	Professional		standard
CABINET	Stainless steel AISI 304		standard
DRUM	Stainless steel AISI 304		standard
HEATING	Electrical	kW	-
	Steam high pressure	bar	3-8
		psi	44-116
CONNECTION	Electrical	3x380-480V	50/60 Hz
		3x208-240V	50/60 Hz
		kW	18,75
	Water inlet	inch	3x1 1/2"
	Steam inlet inch	mm	1"
	Compressed air inlet	mm	Ø8
	Drain	inch	outer Ø mm
			2x103 / 2x4"
DIMENSIONS	Size HxWxD	mm	2085×1855×2085
TRANSPORT DATA	Case packaging	kg	3710
	Net weight	kg	3480
	Volume (packed)	m³	10,16
	Case packaging HxWxD	mm	2340x2000x2170


- = Not available, Standard = Standard execution


The data concerning dimensions of machines include all extended parts.



- 2. Key board
- 3. Emergency stop
- 4. Drain valves
- 5. Steam connection
- 6. Water inlets
- 7. Drum ventilation







SIDE HS 800



