

SUPERIOR CLEANING



**Ergonomic
design**



**Fast drying
cyclus**



**Large
opening**



**Low electricity
consumption**

FEATURES

- ✓ **Standard stainless steel drum with large diameter**
- ✓ **Easy control - Easy to use microprocessor**
- ✓ **Combination of Radial and Axial airflow:**
 - maximal heat transfer
 - low energy consumption
 - short drying time
- ✓ **Large door opening for easy loading and unloading**

OPTIONS

- **Coin operated version**
- **Reversing drum**
- **Professional control - Full control**
- **Residual moisture control:**
 - safe drying of delicate linen
 - humidity detection in %
 - ideal for dry cleaners, fire depts
 - available on Easy and Professional control



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

CAPACITY	Capacity	kg 9
	Drum volume	litres 190
	Drum diameter	mm Ø760
	Number of drums	1
	Number of loading doors	1
AIRFLOW		m³/h 350
DRYING AVERAGE		g/min 150
MOTOR	Fan	kW 0,75
	Drive	kW 0,18
GAS HEATING	Gas connection	inch 3/4"
	Electrical connection	3x 380-415V 50/60 Hz
		3x 220-240V 50 Hz
		3x 208-240V 60 Hz
		3x 440V 60 Hz
Energy	kW 12,5 kBTU/h 42,7	
ELECTRICAL HEATING	Electrical connection	3x 200-240V 50/60 Hz
		3x 380-415V 50 Hz
		3x 380-415/440V 60 Hz
		3x 208-240V 60 Hz
		3x 440V 60 Hz
		3x 480V 60 Hz
Energy	kW 9/12	
PROGRAMMER	Easy control - antivandal (ECT)	standard
	Professional control (FCT)	available
EXHAUST		mm Ø150
DIMENSIONS	Size HxWxD	mm 1465x795x815
TRANSPORT DATA	Gross weight	kg 180
	Net weight	kg 170
	Packing HxWxD	mm 1570x880x885

Standard = Standard version.

