

SUPERIOR CLEANING



Ergonomic
design



Fast drying
cyclus



Large
opening



Low electricity
consumption

FEATURES

- ☑ Standard stainless steel drum with large diameter
- ☑ Easy control - Easy to use microprocessor
- ☑ Combination of Radial and Axial airflow:
 - maximal heat transfer
 - low energy consumption
 - short drying time
- ☑ Large door opening for easy loading and unloading

OPTIONS

- ☐ Coin operated version
- ☐ Reversing drum
- ☐ Professional control - Full control programmer
- ☐ Residual moisture control:
 - safe drying of delicate linen
 - humidity detection in %
 - ideal for dry cleaners, fire depts
 - available on Easy and Professional control



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

CAPACITY	Capacity	kg 2×13
	Drum volume	litres 2×285
	Drum diameter	mm 2×Ø760
	Number of drums	2
	Number of loading doors	2
AIRFLOW		m³/h 1050
DRYING AVERAGE		g/min 2×225
MOTOR	Fan	kW 2×0,75
	Drive	kW 2×0,25
GAS HEATING	Gas connection	NPT 3/4"
	Electrical connection	3x 220-240V 50 Hz
		1x 220-240V 50 Hz
		3x 380-415V 50 Hz
	Energy	kW 2×19,5 kBTU/h 2×66,5
STEAM HEATING	Steam connection	NPT 2×3/4"
	Electrical connection	3x 220-240V 50 Hz
		1x 220-240V 50 Hz
		3x 380-415V 50 Hz
	Steam output *	kW 2×19,5-27
Steam pressure	bar 3-6/7-10	
ELECTRICAL HEATING	Electrical connection	3x 220-240V 50 Hz
		3x 380-415V 50 Hz
		3x 480V 60 Hz
Energy	kW 2×18,0	
PROGRAMMER	Easy control - antivandal (ECT)	standard
	Professional control (FCT)	available
EXHAUST		mm Ø200
DIMENSIONS	Size HxWxD	mm 2030×795×1240
TRANSPORT DATA	Gross weight	kg 385
	Net weight	kg 370
	Packing H×W×D	mm 2120×880×1325

Standard = Standard version. * Steam output is flexible depending on steam pressure.

