

# SUPERIOR CLEANING



**Ergonomic  
design**



**Fast drying  
cyclus**



**Large  
opening**



**Low electricity  
consumption**

## FEATURES

- ✓ **Standard stainless steel drum with large diameter**
- ✓ **Easy control - Easy to use microprocessor**
- ✓ **Combination of Radial and Axial airflow:**
  - maximal heat transfer
  - low energy consumption
  - short drying time
- ✓ **Large door opening for easy loading and unloading**

## OPTIONS

- **Coin operated version**
- **Reversing drum**
- **Professional control - Full control programmer**
- **Residual moisture control:**
  - safe drying of delicate linen
  - humidity detection in %
  - ideal for dry cleaners, fire depts
  - available on Easy and Professional control



# SUPERIOR CLEANING

## DIMENSIONS & SPECIFICATIONS

<b>CAPACITY</b>	Capacity	<b>kg</b> 16
	Drum volume	<b>litres</b> 345
	Drum diameter	<b>mm</b> Ø760
	Number of drums	1
	Number of loading doors	1
<b>AIRFLOW</b>		<b>m<sup>3</sup>/h</b> 600
<b>DRYING AVERAGE</b>		<b>g/min</b> 300
<b>MOTOR</b>	Fan	<b>kW</b> 0,55
	Drive	<b>kW</b> 0,25
<b>GAS HEATING</b>	Gas connection	<b>NPT</b> 3/4"
	Electrical connection	<b>3x 220-240V</b> 50 Hz
		<b>1x 220-240V</b> 50 Hz
		<b>3x 380-415V</b> 50 Hz
	Energy	<b>kW</b> 25
		<b>kBTU/h</b> 85,3
<b>STEAM HEATING</b>	Steam connection	<b>NPT</b> 3/4"
	Electrical connection	<b>3x 220-240V</b> 50 Hz
		<b>1x 220-240V</b> 50 Hz
		<b>3x 380-415V</b> 50 Hz
	Steam output *	<b>kW</b> 22-32
Steam pressure	<b>bar</b> 3-6/7-10	
<b>ELECTRICAL HEATING</b>	Electrical connection	<b>3x 220-240V</b> 50 Hz
		<b>3x 380-415V</b> 50 Hz
		<b>3x 480V</b> 60 Hz
Energy	<b>kW</b> 24	
<b>PROGRAMMER</b>	Easy control - antivandal (ECT)	standard
	Professional control (FCT)	available
<b>EXHAUST</b>		<b>mm</b> Ø200
<b>DIMENSIONS</b>	Size HxWxD	<b>mm</b> 1680x795x1280
<b>TRANSPORT DATA</b>	Gross weight	<b>kg</b> 270
	Net weight	<b>kg</b> 250
	Packing HxWxD	<b>mm</b> 1785x855x1310

Standard = Standard version. \* Steam output is flexible depending on steam pressure.

