

SUPERIOR CLEANING



**Ergonomic
design**



**Fast drying
cyclus**



**Large
opening**



**Low electricity
consumption**

FEATURES

- ☑ Standard stainless steel drum with large diameter
- ☑ Easy control - Easy to use microprocessor
- ☑ Radial airflow with
 - maximal heat transfer
 - low energy consumption
 - short drying time
- ☑ Large door opening (Ø81cm) for easy loading and unloading

OPTIONS

- ☐ Coin operated version
- ☐ Reversing drum
- ☐ Professional control - Full control programmer
- ☐ Residual moisture control:
 - safe drying of delicate linen
 - humidity detection in %
 - ideal for dry cleaners, fire departments
 - available on Easy and Professional control



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

CAPACITY	Nominal	kg 24
DRUM DIMENSIONS	Drum volume	litres 530
	Drum diameter	mm Ø930
AIRFLOW		m³/h 950
DRYING AVERAGE		g/min 384
MOTOR	Fan	kW 0,55
	Drive	kW 0,25
GAS HEATING	Gas connection	inch 3/4"
	Electrical connection	1x 208-240V 60 Hz (3x 380-415V) 50/60 Hz
	Energy	kW 33/39 kBTU/h 112,6/133,1
STEAM HEATING	Steam connection	inch 3/4"
	Electrical connection	1x 208-240V 60 Hz (3x 380-415V) 50/60 Hz
	Energy	kW 27-36,2 kBTU/h 92,1-123,5
ELECTRICAL HEATING	Electrical connection	3x 380-415V 50/60 Hz 3x 480V 60 Hz
	Energy	kW 30/36
PROGRAMMER	Easy control - antivandal (ECT)	standard
	Professional control (FCT)	available
EXHAUST		mm Ø200
DIMENSIONS	Size HxWxD unpacked	mm 1975×965×1270
	Size HxWxD packed	2075×1040×1320
TRANSPORT DATA	Gross weight	kg 300
	Net weight	kg 275

Standard = Standard version. * Steam output is flexible depending on steam pressure.

