

# SUPERIOR CLEANING



**Ergonomic  
design**



**Fast drying  
cyclus**



**Large  
opening**



**Low electricity  
consumption**

## FEATURES

- ✓ Standard stainless steel drum with large diameter
- ✓ Easy control - Easy to use microprocessor
- ✓ Radial airflow with
  - maximal heat transfer
  - low energy consumption
  - short drying time
- ✓ Large door opening (Ø81cm) for easy loading and unloading

## OPTIONS

- Coin operated version
- Reversing drum
- Professional control - Full control programmer
- Residual moisture control:
  - safe drying of delicate linen
  - humidity detection in %
  - ideal for dry cleaners, fire departments
  - available on Easy and Professional control



## SUPERIOR CLEANING

## DIMENSIONS &amp; SPECIFICATIONS

<b>CAPACITY</b>	Nominal	<b>kg</b> 35
<b>DRUM DIMENSIONS</b>	Drum volume	<b>litres</b> 680
	Drum diameter	<b>mm</b> Ø930
<b>AIRFLOW</b>		<b>m<sup>3</sup>/h</b> 1200
<b>DRYING AVERAGE</b>		<b>g/min</b> 560
<b>MOTOR</b>	Fan	<b>kW</b> 0,55
	Drive	<b>kW</b> 0,25
<b>GAS HEATING</b>	Gas connection	<b>inch</b> 3/4"
	Electrical connection	<b>1x 208-240V</b> 60 Hz <b>(3x 380-415V)</b> 50/60 Hz
	Energy	<b>kW</b> 46/50 <b>kBTU/h</b> 157,9/170,6
<b>STEAM HEATING</b>	Steam connection	<b>inch</b> 3/4"
	Electrical connection	<b>1x 208-240V</b> 60 Hz <b>(3x 380-415V)</b> 50/60 Hz
	Energy	<b>kW</b> 39,3-52,7 <b>kBTU/h</b> 134-179,8
<b>ELECTRICAL HEATING</b>	Electrical connection	<b>3x 380-415V</b> 50/60 Hz <b>3x 480V</b> 60 Hz
	Energy	<b>kW</b> 36/48
<b>PROGRAMMER</b>	Easy control - antivandal (ECT)	standard
	Professional control (FCT)	available
<b>EXHAUST</b>		<b>mm</b> Ø200
<b>DIMENSIONS</b>	Size HxWxD unpacked	<b>mm</b> 1975×965×1490
	Size HxWxD packed	2075×1040×1540
<b>TRANSPORT DATA</b>	Gross weight	<b>kg</b> 330
	Net weight	<b>kg</b> 305

Standard = Standard version. \* Steam output is flexible depending on steam pressure.

