

# SUPERIOR CLEANING



**Ergonomic  
design**



**Cylinder heated  
drying ironers**



**High  
production**



**Long-life  
heating  
elements**

## FEATURES

- ✓ Large surface contact with linen over an angle of 300°
- ✓ Highly polished steel, thin cylinder
  - Reasonable price
  - Rapid response to temperature
  - Excellent thermal conductivity
- ✓ Emergency button and Main switch in one
- ✓ Finger protection bar for even more safety
- ✓ Durable Meta Aramid NOMEX® ironing belts
- ✓ Extra heavy press roller for high-quality ironing
- ✓ Patented direct drive – maintenance-free – system
- ✓ Patented central suction system with maintenance-free operation
- ✓ Automatic cool down
- ✓ Easy to operate microprocessor MCX
- ✓ Frequency controlled motor
- ✓ Indication of ironing speed and temperature
- ✓ Space-saving installation against the wall is possible: front return
- ✓ Exhaust outlet at back of the machine
- ✓ Electric or gas heating
- ✓ Metal fibre premix burner (for Gas only)
- ✓ Ergonomic design
- ✓ 3 temperature sensors and overheating check system
- ✓ Adjustable exhaust flap



## OPTIONS

- Coin operated version
- Central payment system operated version (CPS)
- Chrome-plated cylinder for better thermal conduction and ironing quality
- Pedal of insert table stop system
- Exhaust output on the right
- Fixation set for mounting to the floor
- Auto adjustable ironing speed



# SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

		LSR3316 E	LSR3320 E	LSR3316 G	LSR3320 G
<b>ROLLER DIAMETER</b>	<b>mm</b>	320	320	320	320
<b>USEFUL ROLLER LENGTH</b>	<b>mm</b>	1664	2080	1664	2080
<b>CAPACITY*</b>	<b>kg/h</b>	62	70	58	72
<b>SPEED</b>	<b>m/min</b>	1-6	1-6	1-6	1-6
<b>HEATING</b>					
Electric	<b>kW</b>	24.3	27.9		
Gas**	<b>kW</b>	0	0	25	30
<b>MOTOR</b>					
Roller motor	<b>kW</b>	0.18	0.18	0.18	0.18
Fan motor	<b>kW</b>				
Total installed power	<b>kW</b>	24,7	28,3	0,5	0,5
Max. temperature	<b>°C</b>	180	180	180	180
Consumption of electricity	<b>kWh</b>	21,4	27,3	0,5	0,5
Consumption of gas	<b>m³/h</b>			2,62	3,13
Gas types		G20, G25, G30, G31, G110			
Max. gas pressure	<b>mbar</b>			50	50
Noise level	<b>dB (A)</b>	< 57	< 57	< 57	< 57
Ingress protection		IP42	IP42	IP42	IP42
<b>ELECTRIC CONNECTION</b>			380-415V 3AC+N 50/60 Hz		
			208-240V 3AC 50/60 Hz		
			380-415V 3AC-N 50/60 Hz		
			440V-480 3AC 60 Hz (1)	440V-480 3AC 60 Hz	
			208-240V 1AC 50/60 Hz		
<b>DIMENSIONS</b>					
HxWxD	<b>mm</b>	1110x2084x755	1110x2500x755	1110x2084x755	1110x2500x755
Netto Weight	<b>kg</b>	435	490	410	465
Carton packing HxWxD	<b>mm</b>	1260x2190x800	1260x2610x800	1260x2190x800	1260x2610x800
Brutto weight	<b>kg</b>	485	560	465	540

\* According to ISO 9398-1, \*\* For the G20, 20 mbar, (1) max. 456 V

