

SUPERIOR CLEANING



**Ergonomic
design**



**Cylinder heated
drying ironers**



**High
production**



**Long-life
heating
elements**

FEATURES

- ✓ Large surface contact with linen over an angle of 300°
- ✓ High polished steel, thin cylinder
 - Reasonable price
 - Rapid response to temperature
 - Excellent thermal conductivity
- ✓ Finger protection and emergency button for more safety
- ✓ Durable Meta Aramid NOMEX® ironing belts
- ✓ Automatic cooldown
- ✓ Easy to operate microprocessor: 20 pre-set ironing programmes
- ✓ Indication of ironing speed and temperature
- ✓ Reverse mode possible
- ✓ Frequency controlled motor
- ✓ Easy to remove lint filters
- ✓ Space saving installation against the wall is possible: front return
- ✓ Electric, gas or steam heating
- ✓ 3 temperature sensors and overheating check system
- ✓ Ergonomic design



OPTIONS

- Coin operated version
- Central payment system operated version (CPS)
- Chrome-plated cylinder for better thermal conduction
- Pedal of insert table stop system
- Auto adjustable ironing speed



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

		LSR5016	LSR5020	LSR5025	LSR5032
ROLLER DIAMETER	<i>mm</i>	500	500	500	500
USEFUL ROLLER LENGHT	<i>mm</i>	1600	2000	2600	3200
HEATING					
Electric heating	<i>kW</i>	32,4	37,2	54,0	64,8
Gas heating	<i>kW</i>	30	36	52	66
Steam heating	<i>kg/h</i>	36	49	68	88
MOTOR					
Roller motor	<i>kW</i>	0,37	0,37	0,37	0,37
Fan motor	<i>kW</i>	0,18/0,255	0,18/0,255	2x0,18/0,255	2x0,18/0,255
Total installed power					
Electric		33,2	38,0	55,2	66,0
Gas		0,7	0,7	0,9	0,9
Steam		0,7	0,7	0,9	0,9
Exhaust ventilation	<i>mm</i>	1x150	1x150	2x150	2x150
IRONING CAPACITY*					
G20, G25, G30, G31, G110					
Electrical & Gas heating	<i>kg/h</i>	65	80	95	120
Steam heating	<i>kg/h</i>	80	95	115	145
ROLLER SPEED	<i>m/min</i>	1,5-8	1,5-8	1,5-8	1,5-8
ELECTRIC CONNECTION					
380-415V 3AC+N 50/60 Hz, 208-240V 3AC 50/60 Hz					
380-415V 3AC-N 50/60 Hz, 440V-480 3AC 60 Hz					
DIMENSIONS					
HxWxD	<i>mm</i>	1232x2350x1052	1232x2750x1052	1232x3350x1087	1232x3950x1087
TRANSPORT DATA					
Gross Weight	<i>kg</i>	1120	1350	1500	1850
Net Weight	<i>kg</i>	920	1150	1290	1590
Volume (crate packed)	<i>m³</i>	4,24	4,97	6,00	7,03
Crate packing HxWxD	<i>mm</i>	1550x2490x1100	1550x2890x1100	1550x3490x1100	1550x4090x1100

* Tested in accordance of ISO 9398-1.

