

SUPERIOR CLEANING



**Ergonomic
design**



**Cylinder heated
drying ironers**



**High
production**



**Long-life
heating
elements**

FEATURES

- ✓ Large surface contact with linen over an angle of 300°
- ✓ Finger protection and emergency button for more safety
- ✓ Automatic cooldown
- ✓ Easy to operate microprocessor
- ✓ Indication of ironing speed and temperature
- ✓ Reverse mode possible
- ✓ Frequency controlled motor
- ✓ Space saving installation against the wall is possible: front return
- ✓ Electric, gas or steam heating
- ✓ 3 temperature sensors and overheating check system



OPTIONS

- Front or rear return output
- Automatic feeding system
- Vacuum feeding table
- Model LSRA80
 - Frontal and rear output
- Model LSRP80
 - module R with length folding
- Model LSREP80
 - ironer with feeding and length folding
- Module CS – cross folder and stacker (only for LSREP80)



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

		LSR8032	LSRA8032	LSRP8032	LSREP8032
ROLLER DIAMETER	<i>mm</i>	800	800	800	800
USEFUL ROLLER LENGHT	<i>mm</i>	3200	3200	3200	3200
CAPACITY*	<i>kg/h</i>	195	195	195	195
SPEED / SPEED II**	<i>m/min</i>	3-15 / 3-8	3-15 / 3-8	3-15 / 3-8	3-15 / 3-8
HEATING					
Electric heating	<i>kW</i>	75	75	75	75
Gas heating***	<i>kW</i>	110	110	110	110
Steam heating	<i>kg/h</i>	190	190	190	190
MOTOR					
Roller motor	<i>kW</i>	0,75	0,75	0,75	0,75
Fan motor	<i>kW</i>	2 x 0,55/0,75 (50/60 Hz)			
Others	<i>kW</i>	0,2	0,3	0,4	1,1
Fan capacity	<i>m³/h</i>	2 x 1300			
Max. temperature	<i>°C</i>	180	180	180	180
Consumption of electricity	<i>kWh</i>	65,9	66,1	66,2	66,9
Consumption of gas	<i>m³/h</i>	11,40	11,40	11,40	11,40
Consumption of steam	<i>kg/h</i>	190	190	190	190
Gas types		G20, G25, G30, G31			
Max. gas pressure	<i>mbar</i>	60	60	60	60
Noise level	<i>dB (A)</i>	< 75	< 75	< 75	< 75
Ingress protection		IP 42	IP 42	IP 42	IP 42
ELECTRIC CONNECTION					
380-415V 3AC+N 50/60 Hz, 208-240V 3AC 50/60 Hz					
380-415V 3AC-N 50/60 Hz, 440V-480 3AC 60 Hz					
DIMENSIONS					
HxWxD	<i>mm</i>	1985x4260x1915	1985x4260x1915	1985x4260x1915	1985x4260x2010
Netto Weight	<i>kg</i>	E2610/G2480/S2900	E2860/G2730/S3150	E2970/G2840/S3260	E3170/G3040/S3460
Carton packing HxWxD	<i>mm</i>	2080x4380x2080	2080x4380x2080	2080x4380x2080	2080x4380x2080
Brutto Weight	<i>kg</i>	E2870/G2740/S3160	E3120/G2990/S3410	E3230/G3100/S3520	E3430/G3300/S3720

* According to ISO 9398-1, **Lengthwise folding activated, *** G20, 20 mbar

