

SUPERIOR CLEANING



**Ergonomic
design**



**Fast drying
cyclus**



**Large
opening**



**Low electricity
consumption**

FEATURES

- ✓ Full OPL microprocessor
- ✓ Gas, Steam heating, Electrical heating (TD1025R)
- ✓ Large door opening for easy loading and unloading (068cm)
- ✓ Galvanized drum
- ✓ Radial airflow
- ✓ Standard reversing drum
- ✓ Self-cleaning lint screen
- ✓ Preheating of intake air

OPTIONS

- Stainless steel drum
- Stainless steel front panel
- Residual moisture control Sensodry+®:
 - lower energy and utility costs
 - lower linen replacement costs
- SafeTech™ Fire Suppression System



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

CAPACITY	Capacity	kg 77
	Drum volume	litres 1408
	Drum diameter	mm Ø1289
AIRFLOW		litres/s 1156
HEATING	Gas / Steam	kW 116 / 190
MOTOR	Drum	kW 0,560
	Fan	kW 2,238
CONNECTION	Electrical	3x 200-240V 50/60 Hz
		3x 380-415V 50 Hz
		3x 380-415/440V 60 Hz
	Gas inlet	inch 1
	Steam inlet	inch 3/4
DIMENSIONS	H×W×D unpacked	mm 2388×1349×1749
	H×W×D packed	mm 2519×1473×1892
WEIGHT NET	Gas	kg 714
	Steam	kg 760
WEIGHT GROSS	Gas	kg 756
	Steam	kg 806

