## SUPERIOR CLEANING





Fast drying cyclus



Large opening

Low electricity consumption

## FEATURES

- ☑ Full OPL microprocessor
- ☑ Large door opening for easy loading and unloading (068cm)
- ☑ Galvanized drum
- ☑ Radial airflow
- ✓ Standard reversing drum
- ✓ Self-cleaning lint screen
- ☑ Preheating of intake air



## SNOILAC

- □ Stainless steel drum
- □ Stainless steel front panel
- □ Residual moisture control Sensodry+®:
  - lower energy and utility costs
  - lower linen replacement costs
- □ SafeTechTM Fire Suppression System





## SUPERIOR CLEANING

CAPACITY	Capacity		90
	Drum volume	litres	1656
	Drum diameter	mm	Ø1289
AIRFLOW		litres/s	1156
HEATING	Gas / Steam	kW	125 / 190
MOTOR	Drum	kW	0,560
	Fan	kW	2,238
CONNECTION	Electrical	3x 200-240V	50/60 Hz
		3x 380-415V	50 Hz
		3x 380-415/440V	60 Hz
	Gas inlet	inch	1
	Steam inlet	inch	3/4
	Air outlet	mm/inch	305 / 12
DIMENSIONS	H×W×D unpacked	mm	2388×1349×1939
	H×W×D packed	mm	2515×1413×2019
WEIGHT NET	Gas	kg	790
	Steam	kg	820
WEIGHT GROSS	Gas	kg	855
	Steam	kg	855



