

SUPERIOR CLEANING



**Ergonomic
design**



**Fast drying
cyclus**



**Large
opening**



**Low electricity
consumption**

FEATURES

- ✓ Double capacity on the same footprint
- ✓ Easy to use timer
- ✓ Gas, Electrical and Steam heating
- ✓ Large door opening for easy loading and unloading (Ø57cm)
- ✓ Galvanized drum
- ✓ Axial airflow
- ✓ Large lint filter

OPTIONS

- Stainless steel drum
- Stainless steel front panel
- Coin operated version
- Residual moisture control:
 - lower energy and utility casts
 - lower linen replacement casts



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

CAPACITY	Capacity	kg	2×13		
	Drum volume	litres	2×301		
	Drum diameter	mm	Ø762		
AIRFLOW	50 Hz	litres/s	160		
	60 Hz	litres/s	189		
DRYING AVERAGE	Gas heating	g/min	290		
	Electric heating	g/min	313		
MOTOR	Fan	kW	2×0,187		
	Drive	kW	2×0,187		
GAS HEATING	Energy	kW	42,8		
	Energy	kBTU/h	146		
	Gas connection	NPT	1/2"		
	Electrical connection	1×200-240V 50/60Hz	3×200-240V 50/60Hz	3×380-415V 50Hz	3×380-415/440V 60Hz
STEAM HEATING	High pressure 6,9 bar	kW	32,5		
		kBTU/h	111		
	Steam connection	NPT	3/4"		
	Electrical connection	1×200-240V 50/60Hz	3×200-240V 50/60Hz	3×380-415V 50Hz	3×380-415/440V 60Hz
ELECTRICAL HEATING	Energy	kW	21		
	Electrical connection	3×200-240V 50/60Hz	3×380-415V 50Hz	3×380-415/440V 60Hz	
EXHAUST		mm	1x Ø203		
DIMENSIONS	H×W×D	mm	1937×800×1086		
	Net weight	kg	247		
TRANSPORT DATA	Gross weight	kg	264		
	Packing H×W×D	mm	2057×825×1194		

