

SUPERIOR CLEANING



Ergonomic
design



Fast drying
cyclus



Large
opening



Low electricity
consumption

FEATURES

- ✓ Double capacity on the same footprint
- ✓ Easy to use timer
- ✓ Gas, Electrical and Steam heating
- ✓ Large door opening for easy loading and unloading (Ø57cm)
- ✓ Galvanized drum
- ✓ Axial airflow
- ✓ Large lint filter

OPTIONS

- Stainless steel drum
- Stainless steel front panel
- Coin operated version
- Residual moisture control:
 - lower energy and utility casts
 - lower linen replacement casts



SUPERIOR CLEANING

DIMENSIONS & SPECIFICATIONS

CAPACITY	Capacity	kg	2×20
	Drum volume	litres	2×421
	Drum diameter	mm	Ø838
AIRFLOW	50 Hz	litres/s	236
	60 Hz	litres/s	283
DRYING AVERAGE	Gas heating	g/min	376
	Electric heating	g/min	-
MOTOR	Fan	kW	2×0,375
	Drive	kW	2×0,375
GAS HEATING	Energy	kW	51
	Energy	kBTU/h	174
	Gas connection	NPT	1/2"
	Electrical connection	1×200-240V 50/60Hz	3×380-415V 50Hz
STEAM HEATING	High pressure 6,9 bar	kW	-
		kBTU/h	-
	Steam connection	NPT	-
	Electrical connection	1×200-240V 50/60Hz	3×200-240V 50/60Hz
		3×380-415V 50Hz	3×380-415/440V 60Hz
ELECTRICAL HEATING	Energy	kW	-
	Electrical connection	3×200-240V 50/60Hz	3×380-415V 50Hz
		3×380-415/440V 60Hz	
EXHAUST		mm	1x Ø254
DIMENSIONS	H×W×D	mm	2059×876×1235
	Net weight	kg	305
TRANSPORT DATA	Gross weight	kg	326
	Packing H×W×D	mm	2159×902×1372

