## SUPERIOR CLEANING





Fast drying cyclus



Large opening



- ☑ Easy to use timer
- ☑ Electrical, Gas and Steam heating
- ☑ Large door opening for easy loading and unloading (Ø68cm)
- ☑ Galvanized drum
- ☑ Radial airflow
- ☑ Large lint filter

## SNOILAC

- □ Stainless steel drum
- ☐ Stainless steel front panel
- □ Coin operated version
- □ Reversing drum
- □ Residual moisture control:
  - lower energy and utility costs
  - lower linen replacement costs
- ☐ Fire Suppression System







## SUPERIOR CLEANING

CAPACITY	Capacity	ka	25
CAFACITI	Drum volume		528
	Drum diameter		Ø 939
	Drain diameter	***************************************	0 757
AIRFLOW	50 Hz	l/s	354
AII LOW	60 Hz		354
	001.12		
DRYING AVERAGE	Gas Heating	g/min	453
	Electric Heating	g/min	
		<b>9</b>	
MOTOR	Fan	kW	0,375
	Drive		0,375
GAS HEATING	Energy	kW	38,1
	Energy	kBTU/h	
	Gas connection	NPT	1/2"
STEAM HEATING	High presure 6,9 bar	Kw	52
	3 1	kBTU/h	178
	Steam connection	NPT	3/4"
<b>ELECTRICAL HEATING</b>	Energy	kW	30
	0,		
EXHAUST		Ø/mm	203
DIMENSIONS	HxDxW	mm	1946x981x1226
	Net Weight	kg	247
TRANSPORT DATA	Gross Weight	kg	273
	Packing HxWxD	mm	2057x1054x1323
Side T	D-530R Back TD-530R Electric	Back TD-530R Gas Ba	ack TD-530R Steam
			387 mm
1226	mm 981 mm	375 mm	190mm
860 mm			[2 T 2]
		5-116	- 1
	1946 mm		
		1972 mm	1665 mm
1 4		J 1977	9   2
781 mm			
787	340 mm		
<u> </u>	390	ļ <u>_</u>	
749 mm	137 mn	<u>n</u> :	
	838 mm	-	



