## FEATURES

## SUPERIOR CLEANING





Fast drying cyclus



Large opening



Low energy consumption

- ☑ Easy to use timer
- ☑ Electrical, Gas and Steam heating
- ☑ Large door opening for easy loading and unloading (Ø68cm)
- ☑ Galvanized drum
- ☑ Radial airflow
- ☑ Large lint filter

## OPTIONS

- □ Stainless steel drum
- ☐ Stainless steel front panel
- □ Coin operated version
- □ Reversing drum
- □ Residual moisture control:
  - lower energy and utility costs
  - lower linen replacement costs
- ☐ Fire Suppression System







## SUPERIOR CLEANING

CAPACITY	Capacity		l/	g 34
CAPACITI	Drum volume		, A	l 634
	Drum diamete	Ar.	200	n Ø 939
	Didili didiliete	:1	1111	1 10 939
AIRFLOW	50 Hz		11	s 354
AIRFLOW	60 Hz			s 434
	00 HZ		U	\$ 454
DDVING AVEDAGE	Caallaatina		- 1	. (1(
DRYING AVERAGE	Gas Heating			n 616
	Electric Heating		g/m1	n 381
	_			
MOTOR	Fan			V 0,559
	Drive		kl	V 0,559
GAS HEATING	Energy			V 48,3
	Energy		kBTU/	h 165
	Gas connectio	n	NP	T 1/2"
STEAM HEATING	High presure 6	5,9 bar	Kı	v 61,6
			kBTU/	h 210.3
	Steam connec	tion	NP	T 3/4"
<b>ELECTRICAL HEATING</b>	Energy		kl	V 30
EXHAUST			Ø/mr	n 203
DIMENSIONS	HxDxW		mr	n 1946x981x1378
	Net Weight			g 279
				<i>y</i> =
TRANSPORT DATA Gross Weight			lo	g 307
	Packing HxWx	D		n 2057x1054x1433
	I deking HAWAD			1 2037 1203 411433
Side TD-6	i35R	Back TD-635R ElectriC	Back TD-635R Gas	Back TD-635R Steam
				387 mm
1378	mm	981 mm	375 mm	190mm
000			1	
860 mm				
()	<u> </u>	$H \vdash$		$H \vdash \Box$
	1946 mm		1972 mm	
		J 670 mm	1     #	1645 mm
E				
781 mm				
		340 min		
902 mm 838 mm				

